

MODEL HS30


Series 30 Hollow Shaft Encoder

FEATURES

- Up to 1-1/8" or 28.6mm shaft bore diameter
- Heavy Duty bearings
- Unbreakable code disk
- Size 30 housing
- Short circuit and ESD protected
- Up to 1024 pulses per revolution
- Attached cable, or DB9, 16mm or M12 connector
- IP65 protection available - see Model HS31

DIMENSIONS

(shown with DB9 connector, 1-1/8" / 28.6mm shaft bore)



SPECIFICATIONS

Mechanical

Shaft Bore: Any up to 1-1/8" / 28.6mm

Maximum Speed: 6,000 rpm

Shaft Loading:

— Radial: 30 lbs. / 13.6 kg

— Axial: 20 lbs. / 9.1 kg

A flexible mounting bracket is recommended.

Bearing Life: 44 x 1,000,000/rpm = hours

Materials:

— Case: Aluminum, anodized

— Shaft: Aluminum

Weight: 10.5 - 12.5 oz. (298 - 355 grams)

Enclosure rating: IP50

Electrical Connections

Single Ended Outputs:

DB9	16mm	Function	Color
1	1	Common	Black
2	2	Supply voltage	Red
3	4	Output A	White
4	5	Output B	Green
5	3	Output Z	Brown
6-9	6	not used	-

Single Ended Outputs: M12 4-pin

M12	Function	Color
1	Supply voltage	Red / Brown
2	Output B	Green / White
3	Common	Black / Blue
4	Output A	White / Black

Differential Line Driver Outputs:

DB9	16mm	Function	Color
1	5	Common	Black
2	4	Supply voltage	Red
3	1	Output +A	White
4	2	Output +B	Green
5	3	Output +Z	Yellow
6	6	Output -A	Blue/Green
7	7	Output -B	Brown
8	8	Output -Z	Orange
9	-	not used	-

Connectors:

DB9: D-Sub 9-pin.

16mm: Amphenol T3402000 (6-pin) or

T3506000 (8-pin) or equivalent.

M12: 4-pin Turck FS4.4/18.25 or equivalent.

Electrical

Supply Voltages: (specify when ordering)

5Vdc or 8-30Vdc

Current: 50mA max (no load)

100mA max (line driver)

Pulse Rate: 0 - 30 kHz

Pulses per Revolution: (specify when ordering)

1-240, 500, 512, 1000, 1024

Operating Temperature: 0° to 70°C

Output Circuit: (specify when ordering)

Output voltage level is approximately the same as the input voltage level.

Single Ended:

— 7273 open collector

(30 VDC max, 50 mA max)

— 7272 Push-Pull

(50 mA max source or sink)

Differential Line Driver:

— 7272 differential line driver

(also with optional 5vdc output level)

Output Wavehape:

Square wave outputs A and B are 50/50 duty cycle nominal. Output Z (index output) is approximately the width of one cycle on outputs A or B. Output A leads B by 90° for clockwise rotation viewed from shaft collar end.

— Pulse symmetry: 180° ± 30%

— Pulse interval jitter: 30% max

— Quadrature: 90° ± 30% max

— Phase jitter: 30% max

Anti-jitter: (single output models only)

Increases the pulse hysteresis to 1/2 of a pulse width, eliminating the effects of mechanical vibration and possible false output pulses.

For example a 10 pulse per revolution output has 18° hysteresis (i.e. 360° ÷ 10 × 1/2).

Accessories

See our website or contact us for more information about Cables, Mounting Brackets and other accessories.

MODEL NUMBER

HS30	Model Number	Shaft Bore:	Output Type:	Index Output:	Pulses Per Revolution:	Anti-jitter option:	Supply Voltage:	Output Circuit:	Cable/Connector:	Modification Number:	Accessories:
		1.0" = 1" .75 = 3/4" .875 = 7/8", M25 = 25mm, others are available	leave blank for single output on A, Q = quadrature outputs on A and B	leave blank for no index, Z = index output	a number from 1 to 1024 <i>A one-time charge may apply for non-stock values.</i>	leave blank for no anti-jitter, AJ = anti-jitter option (single output models only)	5 or 8-30	leave blank for 7272 Push/Pull, C = 7273 open collector, DH = 7272 line driver, DL = 7272 line driver with 5vdc output level	leave blank for attached 10-ft. / 3-meter cable (other lengths are available)	optional modification or special feature ID. Call or see our website.	leave blank for no accessories. Call or see our website for more information.

Example: HS301.0QZ-1024/8-30DHS1 - 1" shaft bore, quadrature and index outputs, 1024 ppr, 8-30Vdc, 7272 differential line driver, DB9 connector



PO Box 25135 813-886-4000
Tampa FL 33622-5135, USA 800-237-0946
ttco.com • photocraftencoders.com